

Area of Application

ESSVE Blind rivet is a very useful fastener that gives designers immense variation opportunities in product design and material selection.

Description

ESSVE Blind rivet is easy to fit using hand tools or pneumatic tools, it gives a strong, vi-

bration-proof joint with low-on-site costs.

Installation

ESSVE Blind rivet is mounted from one side of the work piece, in drilled or punched holes that should be approx. 0.1 mm larger than the rivet diameter.

Ø mm	Shear stress N	Tensile load N
3.2	500	700
4.0	850	1200
4.8	1200	1700
5.0	1400	2000
6.4	2200	3150

All strength data are average values and are produced from test series and rivet quantity. We recommend that you use these values only as a guide, since many factors other than strength values can affect the riveting result. We recommend that you also test the rivet in your own application to determine the exact function.

Specification

	Rivets	Mandrel
Material	Aluminium EN AW 5154	Bright galvanised steel
Corrosion categories	C2	

Open blind rivet alu/steel, pan head, painted

Colour codes

RAL standard colours	RAL no
White	9003
Black	9011
Brick red	8004
Red	3009

Type AL/ST DIN 7337

Item no.	Dimension d x L mm	Grip area mm	dk mm	k mm	dm mm	Rec. drill mm	Colour	ESSBOX size	Qty/ pack	Pack. / large pack.
62701	3.2 x 8.0	3.0 - 5.5	6.5	0.8	1.8	3.3	White	204	925	6
62703	3.2 x 8.0	3.0 - 5.5	6.5	0.8	1.8	3.3	Black	204	925	6
62705	3.2 x 8.0	3.0 - 5.5	6.5	0.8	1.8	3.3	Brick red	204	925	6
62709	3.2 x 8.0	3.0 - 5.5	6.5	0.8	1.8	3.3	Red	204	925	6
62711	3.2 x 10.0	5.0 - 7.5	6.5	0.8	1.8	3.3	White	204	850	6
62713	3.2 x 10.0	5.0 - 7.5	6.5	0.8	1.8	3.3	Black	204	850	6
62715	3.2 x 10.0	5.0 - 7.5	6.5	0.8	1.8	3.3	Brick red	204	850	6
62719	3.2 x 10.0	5.0 - 7.5	6.5	0.8	1.8	3.3	Red	204	850	6
62721	3.2 x 12.0	7.0 - 9.0	6.5	0.8	1.8	3.3	White	204	775	6
62723	3.2 x 12.0	7.0 - 9.0	6.5	0.8	1.8	3.3	Black	204	775	6
62725	3.2 x 12.0	7.0 - 9.0	6.5	0.8	1.8	3.3	Brick red	204	775	6
62727	3.2 x 12.0	7.0 - 9.0	6.5	0.8	1.8	3.3	Red	204	775	6
62731	4.0 x 8.0	3.0 - 5.5	8.0	1.0	2.2	4.1	White	204	650	6
62733	4.0 x 8.0	3.0 - 5.5	8.0	1.0	2.2	4.1	Black	204	650	6
62735	4.0 x 8.0	3.0 - 5.5	8.0	1.0	2.2	4.1	Brick red	204	650	6
62737	4.0 x 8.0	3.0 - 5.5	8.0	1.0	2.2	4.1	Red	204	650	6
62739	4.0 x 10.0	5.0 - 7.0	8.0	1.0	2.2	4.1	White	204	600	6
62741	4.0 x 10.0	5.0 - 7.0	8.0	1.0	2.2	4.1	Black	204	600	6

