

## Area of Application

ESSVE Self-drilling screw with flange head designed for installing the sheet-metal on beams, sheet-metal on light beams, etc., indoors/outdoors.

## Description

The screw is produced in hardened carbon steel with C4 class Silver CorrSeal surface treatment. Fitted with hex head. The screw

has a Ø14.0 mm flange head on all dimensions except Ø 4.8 mm with a flange head of Ø 10.0 mm. The screw is self drilling and tapping.

## Installation

A screwdriver with adjustable depth stop should be used for quick and efficient installation. Recommended rpm: 1200-2200/min.



## Specification

Material	Hardened steel SAE 1022
Surface treatment	Silver CorrSeal
Corrosion categories	C4

## Self-drilling screw with flange head, CorrSeal

### ESSBOX

Item no.	Dimension dk×L	Drill capacity mm	B = Max grip length mm	Flange Ø	Key width mm	ESS-BOX size	Qty/pack.	Pack./large pack.
63642	4,8 × 19	1,5-3,0	12,0	10,0	8	204	250	6
63644	5,5 × 25	1,5-5,0	17,0	14,0	8	204	250	6
63646	5,5 × 32	3,0-12,0	17,0	14,0	8	204	200	6
63640	5,5 × 38	3,0-12,0	23,0	14,0	8	304	200	4
63648	6,3 × 25	1,5-5,0	17,0	14,0	10	304	250	4
63650	6,3 × 32	1,5-5,0	18,0	14,0	10	304	200	4

