

Area of Application

ESSVE Multi-rivet is a very useful fastener that gives designers immense variation opportunities in product design and material selection. plate and hole variations and efficiently seals against particles and dirt.

Installation

ESSVE Multi-rivet is mounted from one side of the work piece, in drilled or punched holes that should be approx. 0.1 mm larger than the rivet diameter.

ESSVE Multi-rivet is easy to fit using hand tools or pneumatic tools, it gives a strong, v

Description

tools or pneumatic tools, it gives a strong, vibration-proof joint with low-on-site costs. The multi-rivet has very hole filling. Tolerates large

Specification

	Rivets	Mandrel
Material	Aluminium EN AW 5052	Bright galvanised steel
Corrosion categories	C2	

Multi-rivet ventilation, alu/steel, pan head, painted

Colour code RAL

Standard colours	RAL no
White	9003
Black	9011
Brick red	8004
Red	3009

Type MULTI AL/ST

ltem no.	Dimension d x L mm	Grip area mm				Rec. drill mm			Oty/ pack.	Pack. / large pack.
66617	3.2 × 8.0	0.8 - 4.8	6.0	0.9	1.8	3.3	Whit e	204	800	6
66619	3.2 × 8.0	0.8 - 4.8	6.0	0.9	1.8	3.3	Blac k	204	800	6

