

FS-Flex D - Fire sealing system

Area of Application

The elasticity and strength of the Flex D system produces a flexible seal that withstands heavy vibration and movement without cracking, deforming or loosening. The sealant withstands tough work environments within a large temperature range and has very good age resistance.

The system can ideally be combined with other sealing methods, for example, FS-Universal or FS-Flex C.

Description

FS-FLEX D is a complete kit for flexible sealing and repair of small and medium-sized openings

for cables, ventilation ducts and metal pipes. Noise reduction coefficient: 55 dB.

Contains materials for about 5 dm² sealing area.

- Blanket D-24B (backer rod material)
- 2x0.310 l FireStop Sealant 3000 or FireStop 400
- 3 fire sealing labels
- Installation instruction

More information and safety data sheet available on essve.com



Silicone FS-Flex Fire sealing system

Packages

Item no.	Designation	Colour	Contents	Qty/ pack.	Qty/ pallet
100711	FS-Flex D, kit, silicone	White	-	1	72
100712	FS-Flex D, kit, silicone	Grey	-	1	72
100713	FS-Flex D, kit, silicone	Black	-	1	72
100717	FS-Flex D, kit, acrylic	White	-	-	72
100721	FireStop Sealant 3000	White	310 ml	15	1260
100722	FireStop Sealant 3000	Grey	310 ml	15	1260
100723	FireStop Sealant 3000	Black	310 ml	15	1260
100731	FireStop 400	White	310 ml	15	945
100733	FireStop 400	White	600 ml	-	630
100797	Blanket D-24B	-	600×25 mm. 7.3 m	1	16
100798	Blanket D-24B	-	100×25 mm. 7.3 m	1	16
100799	Blanket D-24B	-	100×25 mm. 7.3 m	1	48

