

FS-Universal - Fire sealing system

Area of Application

Fire rated sealant for cables, pipes and ventilation ducts at penetrations in to fire cells boundary structures. The sealant is designed for penetrations with large, free openings and for installations indoors (dry) environments. See the Fire Sealing Guide.

Description

FS-Universal is a complete kit for sealing large penetrations of cables, metal pipes and ventilation ducts in indoor environments (dry). The kit contains the necessary materials for about

18 dm² sealing area. Areas of application, see the Fire Sealing Guide.

Contents: 2 x FS Universal slabs (600x1200x60 mm) of Non-combustible mineral wool with a heat intumescent surface coating, 2 x 0.310 l FireStop Sealant 3000 (white), 0.2 kg Non-combustible mineral wool for caulking, 3 pcs fire seal labels and installation instructions.

Noise reduction coefficient: 51 dB.

More information and safety data sheet available on essve.com



Type approved by SITAC No. 7214/85



Packages

Item no.	Designation	Co-lour	Contents	Qty/ pack.	Qty/ pallet	Re-frac-ted
100740	FS-Universal, kit.	White		1	25	-
100785	Universal 1201	-	Mineral wool slab 600 x 1200 x 60 mm. Single painted	24	24	X
100721	FireStop Sealant 3000	White	310 ml	15	1260	X
100731	FireStop 400	White	0310 ml	15	945	X
100733	FireStop 400	White	600 ml	10	630	-
100767	Non-combustible mineral wool	-	0.2 kg	1		-
100708	Non-combustible mineral wool	-	15 kg	1		-