

FS Flex F - For fire rated joints

Area of Application

FS-Flex F is a type approved joint sealing system intended for vertical or horizontal sealing between different structural parts carried out in fire rating EI 60 to EI 120.

Description

FS-Flex F is a fire sealant system for fire rated joints that consist of fire-resistant sealant, either of the type FireStop Sealant 1000 silicone or FireStop 100 acrylic, together with an approved backing material. The joint sealant is intended to prevent the penetration of

fire, smoke, gas, water, dust and sound. Noise reduction coefficient:
 FireStop 1000: 60 dB.
 FireStop 100: 58 dB.

Contents:

- FireStop Sealant 1000 or FireStop 100
- Blanket D-24B.


More information and safety data sheet available on essve.com

Packages

Item no.	Designation	Colour	Volume	Qty/ pack	Qty/ pallet
100825	FireStop 1000	Grey	310 ml	15	1260
100790	FireStop 1000	White	310 ml	15	1260
100730	FireStop 100	White	310 ml	15	945
100719	FireStop 100	White	600 ml	10	630
100799	Blanket D-24B	-	100 × 25 mm. 7.3 m	1	48



Type approved by SITAC No. 0400/95



FireStop 1000 is BASTA registered. BASTA registration means that we can prove that this building product is in compliance with agreed criteria concerning environmental and health properties. See www.bastaonline.se.