

Area of Application

ESSVE Frame screw L with drill point is designed for the installation of frames for interior doors in steel joist, max 2.0 mm, with wooden joist reinforcement. Frame screw L provides for fully adjustable installation.

Description

It is made of hardened steel with bright zinc plated surface treatment. The screw is designed for step-drilled frames 14/5 mm and is equipped with a TX-drive/bit, TX25.

When the frame screw L is driven into the fra-

me, the barbs under the head grip in the frame. The frame is then adjusted by either screwing the Frame screw L inwards or outwards. The installation is then hidden by a plastic cover.

Installation

The installation is performed in a single step, tight the Frame screw L in the frame and underlying structure.

Installation depth requirement is min. 45 mm in the structure material.



Specification

Material	Hardened steel
Surface treatment	Bright zinc plated

Frame screw L with drill point for steel

ESSBOX

Item no.	Dimension mm	Drill hole mm	Bit no	ESSBOX size	Qty/ pack.	Pack./ large pack.
111107	6×80	14/5	TX25	204	100	6
111109	6×100	14/5	TX25	204	100	6

Small package

Item no.	Dimension mm	Drill hole mm	Bit no	Qty/ pack.
511252	6×80	14/5	TX25	8
511255	6×100	14/5	TX25	8

