

## Construction sealant FAÇADE - Highly elastic expansion joints

### Areas of application

- For indoor and outdoor use
- Between façade/building structure
- Around windows, doors
- Pipes and penetrations
- Construction sealing

### Description

Highly elastic expansion joints (Hybrid sealant). Cures in contact with air, moisture and consequently slowly in tight joints and at lower temperatures, below +5°C, extremely slowly.


- Curing resumes as the temperature rises.
- Frost-proof, water and weather-resistant.
- Clean with cleaning cloth/spray or solvent.
- Weather-resistant
- Soft and low modular
- Working temperature +5°C to +40°C
- Paintable
- Store upright at room temperature +25°C

More information and safety data sheet available on [essve.com](http://essve.com)

### Packages

Item no.	Colour	Colour code	Volume	Qty/pack.	Item code
118501	White	NCS 0502-G	300 ml	12	L
118503	Silicon grey	NCS 2502-Y	300 ml	12	L
118505	Concrete grey	NCS 3502-Y	300 ml	12	L
118507	Black	NCS 9000-N	300 ml	12	L
118509	White	NCS 0502-G	600 ml	12	L
118511	Silicon grey	NCS 2502-Y	600 ml	12	L
118513	Concrete grey	NCS 3502-Y	600 ml	12	L
118515	Black	NCS 9000-N	600 ml	12	L

L = In stock. B = Order item



# BASTA

CONSTRUCTION SEALANT FAÇADE is BASTA registered. BASTA registration means that we can prove that this building product is in compliance with agreed criteria concerning environmental and health properties. See [www.bastaonline.se](http://www.bastaonline.se).

