

Area of Application

ESSVE Nail plug is designed for easier installation of battens, skirting, linings, fittings, cabinets and the like in materials such as concrete, solid brick, stone material and hollow core slab/elements.

Description

A special ribbed nail, pre-fitted in a plug. The plug has a short expansion section for solid homogeneous materials described above. The plug is manufactured of nylon.

Installation (drill-through installation)

Installation

For dimensions 10 mm the plug and nails are supplied separated in the pack and the plug must first be pushed into the hole and then the nail is knocked in. The nail head has a Pozidriv-cross. The nail plug can then be easily removed

See the installation instructions below.



 1. Drill holes with as set out in the Technical data
 2. Press or knock the nail plug into place
 3. Hit the nail with a hammer. For painted 5 mm Nail Plugs use rubber hammer. For dim. 10 mm the

plug and nails are supplied separated in the pack. The plug must first be pushed into the hole and then the nail is knocked in.

Specification

	Bright zinc plated	Bright zinc plated/Pain- ted
Material	Steel	Steel
Corrosion category	C1	C1
Plugs	Polyamide (nylon)	Polyamide (nylon)

Nail plug with countersunk collar, bright zinc-coated ESSBOX

3048015/15/37522PZ220420063048035/25/47522PZ230420043048056/10/40630PZ230420043048076/25/55630PZ230415043048096/37/67637PZ230410043048116/50/80630PZ230410043048138/25/60835PZ230410043048158/40/75835PZ23047543048178/65/100835PZ2304704	ltem no.	Dimensions/Maximum object thickness/L mm	Drill mm	Min. Installation depth mm	Bit no	ESSBOX size	Oty/ pack.	Pack./ large pack.
3048056/10/40630PZ230420043048076/25/55630PZ230415043048096/37/67637PZ230410043048116/50/80630PZ230410043048138/25/60835PZ230410043048158/40/75835PZ2304754	304801	5/15/37	5	22	PZ2	204	200	6
3048076/25/55630PZ230415043048096/37/67637PZ230410043048116/50/80630PZ230410043048138/25/60835PZ230410043048158/40/75835PZ2304754	304803	5/25/47	5	22	PZ2	304	200	4
304809 6/37/67 6 37 PZ2 304 100 4 304811 6/50/80 6 30 PZ2 304 100 4 304813 8/25/60 8 35 PZ2 304 100 4 304815 8/40/75 8 35 PZ2 304 75 4	304805	6/10/40	6	30	PZ2	304	200	4
304811 6/50/80 6 30 PZ2 304 100 4 304813 8/25/60 8 35 PZ2 304 100 4 304815 8/40/75 8 35 PZ2 304 75 4	304807	6/25/55	6	30	PZ2	304	150	4
304813 8/25/60 8 35 PZ2 304 100 4 304815 8/40/75 8 35 PZ2 304 75 4	304809	6/37/67	6	37	PZ2	304	100	4
304815 8/40/75 8 35 PZ2 304 75 4	304811	6/50/80	6	30	PZ2	304	100	4
	304813	8/25/60	8	35	PZ2	304	100	4
304817 8/65/100 8 35 PZ2 304 70 4	304815	8/40/75	8	35	PZ2	304	75	4
	304817	8/65/100	8	35	PZ2	304	70	4
304819 8/85/120 8 35 PZ2 304 60 4	304819	8/85/120	8	35	PZ2	304	60	4
304821 10/50/100 10 50 PZ2 206 35 4	304821	10/50/100	10	50	PZ2	206	35	4
304823 10/70/120 10 50 PZ2 206 35 4	304823	10/70/120	10	50	PZ2	206	35	4



Small package

ltem no.	Dimensions/Maximum object thickness/L mm		Min. Installation depth mm	Qty/ pack.	
511344	5/15/37	5	22	10	10
511345	5/22/47	5	25	10	10



ltem no.	Dimensions/Maximum object thickness/L mm	Drill mm	Min. Installation depth mm	Bit no	Qty/ pack.	Pack./ large pack.
511346	6/25/55	6	30		10	10
511348	6/50/80	6	30		10	10
511349	8/65/100	8	35		10	10
511350	8/85/120	8	35		10	10
513114	5/15/X37	5	22		25	6
513115	5/22/47	5	25		25	6
513116	6/25/55	6	30		20	6
513118	6/50/80	6	30		20	6
513122	8/65/100	8	35		20	6
513123	8/85/120	8	35		20	6

Bulk packages

Item no.	Dimensions/Maximum object thickness/L mm	Drill mm	Min. installation depth mm	Qty/ pack.
7304745	8/30/70	8	40	600
7304771	8/60/100	8	40	400
7304773	8/80/120	8	40	200