

## Area of application

ESSVE Offset bracket is designed for use on all types of simple cross joint, where timber, to a large extent can work freely, without tensioning. This eliminates the risk of cracking.


## Description

Made of 2.0 mm hot dip galvanized sheet steel and fitted with 5.0 mm holes. Available in

right and left-hand designs.

## Installation

Connectors are installed using 4.0 mm anchor nails or 5.0 mm wood connector screws. Must be fitted with 2 connectors per cross-joint, diagonally/symmetrically towards each other.



## Specification

Material	Steel S250GD
Lower yield point value, fyk	Min. 250 MPa
Surface treatment	Hot dip galvanized 20 µm
Corrosion category	C2
Nail hole Ø	5.0 mm

## Offset bracket right and left, hot dip galvanized



Type		Dimensions a x b x c x d mm	Hole Anchor nail/ Wood connector screw Quantity / flange x Ø mm	CE marked	Qty/ pack.	Qty. / pallet	Item code
Item no.							
<b>451280</b>	170 V	32×100×144×2.0	9+9×Ø5.0	CE	100	8000	L
<b>451277</b>	170 H	32×100×144×2.0	9+9×Ø5.0	CE	100	8000	L
<b>451289</b>	210 V	32×140×189×2.0	13+13×Ø5.0	CE	100	4800	L
<b>451286</b>	210 H	32×140×189×2.0	13+13×Ø5.0	CE	100	4800	L

L = In stock, D = Direct delivery, 4 week delivery time