

### Area of Application

ESSVE Golden Anchor is designed for fastening in concrete and natural stone. Ideally Golden Anchor can be used in applications where high load demands are

made on the fixing. Golden Anchor can for example be used when fixing wooden studs/steel joists as well as sills and facade studs, fixing brackets, z-iron, wrought iron designs, etc.



### Small package

Item no.	Dimension/Detail thickness/Length mm	D mm	Th-read length mm	Drill Ø mm	Drill depth mm	Max detail thick.m	Key width	Qty./ pack.	Pack / large pack
<b>5107 21</b>	M8/10/86	18	50	8	40/60/70	40/20/10	13	3	10
<b>5107 22</b>	M8/50/126	18	66	8	40/60/70	80/60/50	13	3	10
<b>5107 24</b>	M10/7/104	22	59	10	45/65/90	51/31/7	15	3	10
<b>5137 24</b>	M10/7/104	22	59	10	45/65/90	51/31/7	15	10	6
<b>5107 25</b>	M10/37/134	22	89	10	45/65/90	81/61/37	15	2	10
<b>5107 26</b>	M10/52/149	22	89	10	45/65/90	96/76/52	15	2	10
<b>5137 26</b>	M10/52/149	22	89	10	45/65/90	96/76/52	15	8	6
<b>5107 17</b>	M12×80*	26	34	12	85/-	5/-	18	2	10
<b>5107 28</b>	M12/15/126	26	70	12	85/100	31/15	18	2	10
<b>5137 28</b>	M12/15/126	26	70	12	85/100	31/15	18	6	6
<b>5107 30</b>	M12/45/156	26	70	12	85/100	61/45	18	2	10

\* These dimensions are too short to meet the requirement for the standard installation depth