

Area of Application

ESSVE Drywall screws are intended for the installation of Drywall boards indoors against wooden joists.

Description

The screw is straight collated and manufactured of hardened carbon steel with bright zinc plated surface treatment. It is equipped with Philips crosshead Ph2.

ESSVE Drywall screws for wooden joists are

suitable for the most common auto-feed screwdrivers available on the market, e.g. Makita, Hilti, Kartro, Hitachi and others.

Installation

Machined bits are recommended when fitting collated drywall screws.

Recommended rpm: 30-55 mm 2800-4700/min



Specification

Material	Hardened steel SAE1018
Surface treatment	Bright zinc plated 5 µm
Usage	Approx 20 per m ²
Corrosion categories	C1

Drywall screw for wooden joists, bright zinc plated

Item no.	Dimension dk × L mm	D mm	B mm	Bit no	Qty/pack.	Pack./large pack.	Quantity / pallet
532330	3,9 × 30	8,4	25,0	PH2	1000	6	144
532335	3,9 × 35	8,4	30,0	PH2	1000	6	144
532340	3,9 × 41	8,4	36,0	PH2	1000	6	144
532350	3,9 × 50	8,4	45,0	PH2	1000	6	108
532355	3,9 × 55	8,4	50,0	PH2	1000	6	108

