

Area of Application

ESSVE drywall screw outside GU Combi, is intended for installation of drywall boards outdoor on outer walls against wooden or steel joists. Drill capacity 0.4-0.9 mm.

Description

ESSVE Drywall screw GU Combi, is a newly developed screw with a flat surface-mounted head.

This design provides a weatherproof installation before the façade cladding is fitted.

The design of the screw conforms to the requirements set out in HusAMA 98 on the installation of outside drywall boards, KBC.111.

The screw is fitted with a combi thread which makes it suitable for installing against wooden

or steel joists max. 0.9mm. The screw is made of hardened steel with silver CorrSeal surface treatment, making it suitable for use in outdoor environments. The silver CorrSeal surface treatment realises corrosivity category C4.

ESSVE Drywall screw GU combi is suitable for the most common autofeed screwdrivers available on the market.

Installation

A screwdriver with adjustable depth stop should always be used to ensure correct, quick and efficient installation. The screw must not be countersunk, the surface finish of the board must not be damaged. Recommended rpm: 30 - 40 mm 2800 - 6000/min.



CorrSeal

ESSVE CorrSeal surface treatment.



Type approved by SITAC No. 0075/05

Specification

Material	Hardened steel SAE 1022
Surface treatment	CorrSeal, wax
Usage	About 20/m ²
Corrosion category	C4

Drywall screw GU outdoor, combi, for wooden/steel joists, CorrSeal

Technical data and packing

Item no.	Dimension dk x L mm	D mm	B mm	Bit no	Qty/pack.	Pack./large pack.
536330	3.9 x 30	9.0	26.0	PH2	1000	6
536340	3.9 x 40	9.0	36.0	PH2	1000	6

