

### Area of Application

ESSVE Drywall screw with drillpoint designed for the installation of Drywall boards indoors against steel joists. Drill capacity 0.7-2.0 mm.

### Description

The screw is straight collated and manufactured of hardened steel with phosphated, bright zinc plated 5 µm or bright zinc plated 20 µm as the surface treatment. It is equipped with Philips crosshead Ph2.

### Specification

	Phosphated	Bright zinc plated	Bright zinc plated
Material	Hardened steel SAE1018	Hardened steel SAE1018	Hardened steel SAE1018
Surface treatment	Phosphated	Bright zinc plated 5 µm	Bright zinc plated 20 µm
Usage	Approx 20 per m <sup>2</sup>	Approx 20 per m <sup>2</sup>	Approx 20 per m <sup>2</sup>
Corrosion categories	C1	C1	C2

ESSVE Drywall screws with drillpoint are suitable for the most common auto-feed screwdrivers available on the market.

### Installation

Machined bits are recommended when fitting collated drywall screws.

Recommended rpm: 25-50 mm 2000-2800/min



### Drywall screw with drillpoint for steel joists, phosphated

Item no.	Dimension dk × L mm	D mm	B mm	Bit no	Qty/pack.	Pack./large pack.	Quantity/pallet
581325	3,5 × 25	8,4	20,0	PH2	1000	6	144
581340	3,5 × 40	8,4	35,0	PH2	1000	6	144
581350	3,5 × 50	8,4	45,0	PH2	1000	6	108

