

Area of Application

ESSVE Drywall screw with drillpoint designed for the installation of Drywall boards indoors against steel joists. Drill capacity 0.7-2.0 mm.

Description

The screw is straight collated and manufactured of hardened steel with phosphated, bright zinc plated 5 µm or bright zinc plated 20 µm as the surface treatment. It is equipped with Philips crosshead Ph2.

Specification

	Phosphated	Bright zinc plated	Bright zinc plated
Material	Hardened steel SAE1018	Hardened steel SAE1018	Hardened steel SAE1018
Surface treatment	Phosphated	Bright zinc plated 5 µm	Bright zinc plated 20 µm
Usage	Approx 20 per m ²	Approx 20 per m ²	Approx 20 per m ²
Corrosion categories	C1	C1	C2

ESSVE Drywall screws with drillpoint are suitable for the most common auto-feed screwdrivers available on the market.

Installation

Machined bits are recommended when fitting collated drywall screws.

Recommended rpm: 25-50 mm 2000-2800/min



Drywall screw with drillpoint for steel joists, bright zinc plated 20 µm

Bright zinc plated 20 µm

Item no.	Dimension dk × L mm	D mm	B mm	Bit no	Qty/pack.	Pack./large pack.	Qty/pallet
591325	3,5 × 25	8,4	20,0	PH2	1000	6	180