

Area of Application

ESSVE Arrow Anchor is an anchor for easier installation in drywalls, incl. soft board or light-weight concrete. Works in single and double drywall.

Description

The anchor is knocked into the drywall using a hammer, a screw is then screwed in that ex-

pands the anchor while securing the object to hung up.

Suitable screw to use, for example, a drywall screw with a diameter of 3.5 to 3.9 mm. The length of the screw is determined by the detail to be installed.



Installation

1. Knock the anchor into the drywall.
2. Screw a drywall screw, Ø 3.5 to 3.9 mm.
3. The anchor expands at the back and secures the object to hang up.

Specification

Material	Steel
Surface treatment	Yellow zinc plated

Drywall anchor Arrow Anchor

Technical data and ESSBOX pack

Item no.	Designation	ESSBOX size	Qty/ pack.	Pack. / large pack.
64503 8	Arrow Anchor (without screw) 3.5 mm	202	100	12
511644	Arrow Anchor (without screw) 3.5 mm (small package)		8	10
96450 38	Arrow Anchor (without screw) 3.5 mm (bulk)		500	1
			0	

Designation	Single drywall kg	Double drywall kg
	Tension load (N)/Shear load (V)	Tension load (N)/Shear load (V)
Arrow Anchor	10/20	15/30
Safety factor 3.0		

