

Area of Application


ESSVE Wing screw with drillpoint designed for the installation of timber and sheet materials indoors against steel joists and outdoors.

Description

The screw is produced in hardened carbon steel with CorrSeal surface treatment, C4 classified. A drilling and self-tapping screw equipped with the wings for clearance drilling in soft materials. The head is equipped with cutting grooves that countersinks the screw during installation. Equipped with Philips crosshead Ph2, Ph3 or TX depending on the dimensions.

Installation


Recommended rpm approx. 1400-2200/min.



Specification

Material	Hardened steel SAE C1022
Surface treatment	CorrSeal
Environment/Corrosion category	C4

Wing screw for steel joists, CorrSeal. TX drive ESSBOX





Item no.	Dimension mm	D mm	B mm	Bit no	Maximum grip length at maximum drilling capacity	Drill capa- city mm	ESSBOX size	Qty./ pack.	Pack./ large pack.
695138	$4,8 \times 38$	9,5	20,5	TX25	26,0	2,5-4,0	203	250	8
695145	$4,8 \times 45$	9,5	27,5	TX25	33,0	2,5-4,0	204	250	6
695165	$4,8 \times 65$	9,5	47,5	TX25	53,0	2,5-4,0	304	250	4
695185	4,8 × 85	9,5	67,5	TX25	73,0	2,5-4,0	304	200	4