

## Area of application


ESSVE Fixing band is designed for stabilising and bracing timber structures.

## Description

Made hot dip galvanized sheet steel and fitted with 5.0 mm holes.

## Installation

The band is installed using e.g. ESSVE Anchor nails 4.0 mm or ESSVE Wood connector screws 5.0 mm. When installing the band must be stretched with ESSVE Strap tensioner and anchored in each joist or truss.



## Specification

Material	Steel S250GD
Lower yield point, fyk	Min. 250 MPa
Surface treatment	Hot dip galvanized 20 µm
Corrosion category	C2
Nail hole	5.0 mm
Length/pack.	25 m and 50 m


## Strapping band

Item no.	Dimensions mm	Hole Ø mm	Length/ pack. m	Practical load capacity for the band* kN	Qty/ pack.	Qty/ pallet	Item code
<b>396660995</b>	60x2.0	5.0	50	17.0	50	20	L

\* Check the number of nails required. L = In stock, D = Direct delivery, 4 week delivery time.



40 x 2,0/3,0 mm Ø5,0



60 x 2,0 mm Ø5,0



Item no.	Dimensions mm	Hole Ø mm	Length/ pack. m	Practical load capacity for the band *kN	CE marked	Qty/ pack.	Quantity / pallet	Item code
<b>451499</b>	40x1.5	5.0	25	11.3	CE	1	40	L
<b>451496</b>	40x2.0	5.0	25	17.0	CE	1	20	L

\* Check the number of nails required.